

PIPE WITH LATCH & LATCH FITTINGSS

PIPE WITH LATCH

DIAMETER	LENGTH
mm	m
50	5
50	6
63	6
63	12
75	6
75	12
90	6
110	6
125	6
140	6
160	6



CROSS ELBOW

DIAMETER
mm
50 x 50
63 x 50
63 x 63
75 x 50
75 x 63
75 x 75
90 x 50
90 x 63
90 x 75
90 x 90
110 x 50
110 x 63
110 x 75
110 x 90
110 x 110
125 x 50
125 x 63
125 x 75
125 x 90
125 x 110
125 x 125
140 x 50
140 x 63
140 x 75
140 x 90
140 x 110
140 x 125
140 x 140
160 x 50
160 x 63
160 x 75
160 x 90
160 x 110
160 x 125
160 x 140
160 x 160

TEE

DIAMETER
mm
50 x 50
63 x 50
63 x 63
75 x 50
75 x 63
75 x 75
90 x 50
90 x 63
90 x 75
90 x 90
110 x 50
110 x 63
110 x 75
110 x 90
110 x 110
125 x 50
125 x 63
125 x 75
125 x 90
125 x 110
125 x 125
140 x 50
140 x 63
140 x 75
140 x 90
140 x 110
140 x 125
140 x 140
160 x 50
160 x 63
160 x 75
160 x 90
160 x 110
160 x 125
160 x 140
160 x 160



REDUCER

DIAMETER
mm
75 x 50
75 x 50
90 x 63
90 x 50
110 x 63
110 x 75
125 x 50
125 x 63
125 x 75
140 x 75
140 x 90
140 x 110
140 x 125
160 x 90
160 x 110
160 x 125

ELBOW

DIAMETER
mm
50
63
75
90
110
125
140
160



LATCH FITTINGSS

HEAD MALE



DIAMETER
mm
50
63
75
90
110
125
140
160

HEAD FEMALE



DIAMETER
mm
50
63
75
90
110
125
140
160

PLUG MALE



DIAMETER
mm
50
63
75
90
110
125
140
160

PLUG FEMALE



DIAMETER
mm
50
63
75
90
110
125
140
160

SPRINK ABOT



DIAMETER
mm
50
63
75
90
110



PVC RISER

SIZE	
inch	mm
1"	25
1"	33
1"	50
1"	60
1"	75
1"	100
1"	120
1"	150

PUMP CONNECTION MALE



DIAMETER
mm / inch
50 x 2
63 x 2
75 x 2 1/2"
90 x 3
110 x 4
125 x 5
140 x 5
160 x 6



PUMP CONNECTION FEMALE

DIAMETER
mm / inch
50 x 2
63 x 2
75 x 2 1/2"
90 x 3
110 x 4
125 x 5
140 x 5
160 x 6



LATCH FITTINGSS

LINE VALVE



DIAMETER
mm
50
63
75
90
110
125
140
160

BALL VALVE



DIAMETER
inch
1"

SPRING ADAPTER



DIAMETER
inch
20 x 1/2"

CROSS ABOVE ABOT



DIAMETER
mm / inch / mm
20 x 1" x 20

COUPLING



DIAMETER
mm / inch
3/4" x 3/4"
3/4" x 1/2"
1" x 1/2"
1" x 3/4"
1" x 1"

GASKET



DIAMETER
mm
50
63
75
90
110
125
140
160

ADDITIONAL PARTS



DIAMETER
mm
50 - 63 - 75
90 - 110
125 - 140 - 160



SPRINKLERS



AG1/2MS1

Diameter, inch	1/2"
Nozzle, mm	2,8 x 1,8 3,2 x 1,8 3,2 x 2,3
Pressure, bar	2,5- 3,5
Range, m	21- 23
Flux, m3/h	740- 1397



AG1/2MS2

Diameter, inch	1/2"
Nozzle, mm	4
Pressure, bar	0,5- 2,5
Range, m	5- 10
Flux, l/min	14,8- 28



AG3/4FS4

Diameter, inch	1/2", 3/4"
Nozzle, mm	4
Pressure, bar	1,3- 3,0
Range, m	6- 13
Flux, l/min	14,8- 28



AG1FS52

Diameter, inch	1"
Nozzle, mm	
Pressure, bar	2,0- 4,0
Range, m	16- 18
Flux, m3/h	4,8- 5,7



AG3/4FS23

Diameter, inch	1"
Nozzle, mm	4,5 x 5,0 2,3 x 3,8
Pressure, bar	2,0- 3,5
Range, m	25- 30
Flux, l/min	1160- 3000



AG1HS25

Diameter, inch	1"
Nozzle, mm	16 x 24
Pressure, bar	2,0- 4,0
Range, m	12- 20
Flux, m3/h	2- 6,5



AG3/4FS49

Diameter, inch	3/4"
Nozzle, mm	5,0 x 3,8 5,0 x 4,0 3,8 x 2,3
Pressure, bar	1,5- 3,5
Range, m	12- 14
Flux, m3/h	1,3- 1,7



AG1HS30 / 360°

Diameter, inch	1,5"
Nozzle, mm	8 x 18
Pressure, bar	2,0- 6,0
Range, m	15- 30
Flux, m3/h	5- 25



AG3/4MS301

Diameter, inch	3/4"
Nozzle, mm	5,0 x 2,8
Pressure, bar	3,0- 5,0
Range, m	13- 18
Flux, l/min	11,6- 41



AG2P50

Diameter, inch	2"
Nozzle, mm	16 x 26
Pressure, bar	2,0- 7,0
Range, m	26- 53
Flux, m3/h	17,8- 75



AG3/4FS45

Diameter, inch	3/4"
Nozzle, mm	5,0 x 2,5
Pressure, bar	0,5- 4,0
Range, m	3- 16,5
Flux, l/min	6,8- 32,4



AG15/25PY

Type	PY30	PY40	PY50
Diameter, inch	1,5"	2"	2,5"
Nozzle, mm	10 x 3,5	14 x 7,5	20 x 3,5
Pressure, bar	3,0- 4,5	3,0- 4,0	4,0- 5,0
Range, m	23- 25	25- 30	30- 40
Flux, m3/h	7- 9	17- 20	30- 35



AG1FS50

Diameter, inch	1"
Nozzle, mm	
Pressure, bar	2,0- 5,0
Range, m	15- 17
Flux, m3/h	3,7- 5,0